

Push-type Detector Switches

SW-110 Series

Features


- ◇Miniaturized for space saving design.
- ◇Superior reliability at micro-current by employing a sliding contact.
- ◇Available in wide variety of mounting methods , operating methods etc.

Applications

- ◇Mechatronic detection for audio and VCR CD-ROM DVD units.

Products Number System

SW - [] [] [] - [] []



Actual size

Products Line

No	Products No	Pole	Position	Operating force	Notes
1	SW-110	1	1	0.5N max.	
2	SW-111	1	1	0.5N max.	

Typical Specifications

Item	Specification
Ratings (max.)	100mA 12V DC (Resistive load)
Contact resistance	1 ohm max.
Insulation resistance	100 megohm min. 100V DC
Withstanding voltage	100V AC for 1min.
Operating life with load	50,000 cycles

Dimensions

Unit : mm

No	Style	P.C.B reference mounting hole Dimensions , Circuit diagram (TOP VIEW)
1		
2		

Notes

- The appearance and specifications of the product may be modified to improve its performance without prior notice.
- This catalog shows only outline specifications. When using the product, please obtain formal specifications.
- Please see appendix [Cautions in Using Switches].
- This switch is not washable.
- Soldering shall be done with actuator at free position and take care not to attach flux on plastic portion.
- Note that if the stress is applied to the terminals during soldering, they might cause deformation and defects in electrical performance.
- In manual soldering, consideration should be given to apply the soldering iron to the tip of the terminal so that unusual pressure is not applied to the terminal.
- In case circuit and software design consideration against chattering and bouncing shall be taken as below.
 - Read a few times. (Ex. 5ms for 5 times)
 - Set delay time.
 - Set integral circuit.
- As to threshold voltage, center setting is recommended.
- Care shall be taken not to apply stress to the body of switch as it may affect the performance.
- When mounting the switch on a metal chassis, be careful not to short-circuit between the exposed metal part of the switch and the chassis.
- Please confirm the performance on actual operation by simulation with actual environment environments for high reliability.